

INSTALLATION INSTRUCTIONS

Item#1226-xxx (New. 2024/06/11)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
VERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Lower shade (K) down over fixture body (O). Pass fixture wires through hole in bracket on top of shade (K) and through coupling (L). Thread coupling (L) onto all thread protruding through bracket on shade (K). Tighten coupling (L) to secure shade (K) in place.
4. Determine the desired hanging height and threads rod (M/N). Carefully feed wires through each rod as you assemble.
5. Thread rod (N) onto coupling (L).
6. Push fixture wires up through loop (S). Pull fixture wires taut. Thread loop (S) onto top of last rod. Slip fixture wires through hole on threaded ring (F) and through hole in canopy (D).

HANGING THE FIXTURE (Fig. 2)

7. Attach crossbar assembly to junction box (Not included) using junction box screw (B). The side of crossbar (A) marked "GND" must face out. The length of all thread into crossbar (A) may be adjusted if necessary. Then tighten with hex nuts provided.
8. Thread screw collar loop (W) onto end of all thread attached to crossbar (A).
9. Push fixture wires up through hole in screw collar loop (W) attached to crossbar (A) and out end of all thread inside junction box.

CONNECTING THE WIRE (Fig. 3)

10. Connect the electrical wire as shown in Fig.3. Making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect fixtures ground wire to it. Otherwise, connect fixture ground wire directly to the crossbar using green screw provided.
11. Tuck wire connections neatly into the outlet box.

FINISHING THE FIXTURE (Fig.1)

12. Attach lock link (G) to loop (S) on rod and thread collar loop (W).
13. Raise canopy (D) up to ceiling. Secure canopy (D) to ceiling with threaded ring (F).
14. Install (6) six candelabra base bulbs up to 60 watts each or CFL or LED equivalent (Not included), in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.

Your installation is now complete. Return power to the outlet box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

