INSTALLATION INSTRUCTIONS FOR 140-899 For PENDANT

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER AVERTISSEMENT!COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DO DISJONCTEU

ASSEMBLING THE FIXTURE (Fig.1)

- Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- Attach the mounting plate (A) to the junction box (Not included) using mounting screws (C) (Size: 8-32*1/2"L).
 The side of the mounting plate (A) marked "GND" must face out.
- Determine desired hanging height and thread rods (G1/G2) to all thread (H). Carefully feed fixture wire carefully through each rod as you assemble. IMPORTANT: At least one rod must be used.
- 4. Secure rods to the swivel (F) on canopy.

CONNECTING THE WIRES (Fig.2)

- 5. Connect the electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to mounting plate using green screw (B) provided.
- 6. Tuck wire connectors neatly into the junction box.

COMPLETING THE INSTALLATION

- Place canopy (E) over mounting plate (A) and secure with screws (D).
- Install (1) one candelabra base bulb up to 60 watts or CFL or LED equivalent (Not included), in accordance with the fixture specification (DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSNCE NOMINALE MAXIMLE!)
- 9. Secure glass (J) to fixture (I) by twisting and locking into place. Do not over tighten.

Your installation is now complete. Return power to the junction box and test the fixture.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.







