

INSTALLATION INSTRUCTIONS

Item#3605-732,3606-732

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
VERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Rotate arms until they are properly aligned with center of fixture body. Arms should tighten as they are rotated to proper position turned. Place arm assembly (N) on fixture body (P).
4. Pass all thread (K) through Abaca rod (L) to thread onto arm assembly (N), decorative cover (J) and washer (Q) provided.
5. Position small decorative cover (J) on Abaca rod (L) and thread rods (H/D). Determine the desired hanging height and thread rod (H/D). Carefully feed wires through each rod as you assemble.
6. Push fixture wires through swivel (G), screw collar ring (F), canopy (E) and all thread (C). Thread swivel (G) to rod (H/D).

HANGING THE FIXTURE (Fig. 2)

7. Slip screw collar ring (F) and canopy (E) over swivel (G) and allow them to rest on rod (H/D). Thread swivel (G) to all thread (C).
8. Attach crossbar assembly to junction box (Not included) using junction box screw (B). The side of crossbar (A) marked "GND" must face out. The length of all thread into crossbar (A) may be adjusted if necessary. Then tighten with hex nuts provided.
9. Push fixture wires through all thread inside junction box.

CONNECTING THE WIRE (Fig. 3)

10. Connect the electrical wire as shown in Fig.3. Making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect fixtures ground wire to it. Otherwise, connect fixture ground wire directly to the crossbar using green screw provided.
11. Tuck wire connections neatly into the outlet box.

FINISHING THE FIXTURE (Fig.1)

12. Position canopy (E) up against ceiling and thread screw collar ring (F) to secure fixture to ceiling.
13. Install (6) six candelabra base bulbs up to 60 watts each or CFL or LED equivalent (Not included), in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
14. Place Abaca shade on arm assembly (N) and secure with knobs (M).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig.1




Fig. 2




Fig. 3

