INSTALLATION INSTRUCTIONS

Item#3682-886 (New. 2024/12/13)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

- Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
- Thread canopy screws (C) into pre-drilled holes on mounting plate (A). Spaced same distance apart as holes in mounting plate (A), and secure with nuts (D) provided. The length of canopy screws (C) may be adjusted if necessary.
- Attach mounting plate (A) using mounting screws (B) (Size: #8-32N*L1") to outlet box (Not included). The side of the mounting plate marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

- 5. Connect electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to mounting plate using green screw provided.
- 6. Tuck wire connections neatly inside outlet box.

FINISHING THE INSTALLATION (Fig.1)

- 7. Place fixture body (E) over mounting plate (A), and secure with cap nuts (F).
- Install (2) two candelabra base bulbs up to 60 watts each or CFL or LED equivalent (included) in accordance with the fixture specification DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- 9. The Lampshade install onto the fixture body (E).

Your installation is now complete. Return power to the outlet box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

MIN 75°C SUPPLY CONDUCTORS.





