INSTALLATION INSTRUCTIONS

For Model 72486-143C/72486-66-C

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

HANGING THE FIXTURE (Fig. 1)

- 1. Shut off the power at the circuit breaker and remove the old fixture including the mounting hardware.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.

CONNECTINE THE WIRES (Fig.2)

- 3. While supporting the fixture, connect the electrical wires as shown in Fig. 2. If your post has a ground wire (green or bare copper), connect fixture ground wire to it. If not, consult your electrician for proper grounding.
- 4. After the wires are connected, tuck them carefully inside the post cup (A).

COMPLETING THE INSTALLATION (Fig. 1)

- **5.** Install the bulb (E12-Candelabra, not included) in accordance with the fixture's specification.
- **6.** Attach the top cover (E) to the cage (C) and secure with screws (D).
 - DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- 7. Place the fixture onto post cup (A), and secure with screws (B).

Your installation is now complete. Return power to the junction box and test the fixture.





