



#### **MEASUREMENTS**

Blade Finish:	·
Blade Material:	ABS
Blade Sweep:	60"
No. of Blades:	3
Blade Pitch:	12°
Reversible Blades:	NO
Slope:	NO
Hanging Weight:	17.59
Downrod 1:	10
Downrod 1 Outside Dia:	.75
Downroad 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	18.18
Ceiling to Blade (Dim B):	16.61
Lead Wire:	80"
Power:	DC
Motor Size:	DC 172x12MM

	Low	Low/Med.	Medium	Med/High	High
	LOW	LOW/IVICG.	Wicaram	Wicarriigii	riigii
RPM	49				148
Amps	0.04				0.45
Watts	2.3				28.07
CFM	1859.0				6349.0
CFM/Watts	808.26				226.18

### LAMPING

No. of Bulbs:	0
Max Bulb Wattage:	20
Light Type:	LED MODULE
Light Kit Optional:	NO
Socket:	INTEGRATED LED
Integrated Light Kit:	YES
Dimmable:	YES
Ballast:	
Rated Life Hours:	50000
Uplight:	NO
Bulb/LED Included:	YES
Color Temp.:	3000
CRI:	90
Initial Lumens:	1900.0
Delivered Lumens:	1500.0

# Switch - 60" LED Smart Dual Mount Ceiling Fan

F636L-CL
706411071386
Switch
Black Coal
INTERIOR FAN
Ceiling Fan
4000048

Notes













### GLASS

Description:	WHITE
Material:	ETCHED PC LENS
Part No.:	
Quantity:	1
Width:	6.4
Height:	1.1
Length:	

## CONTROLS

Pull Chain Control:	NO
Works with Remote Control:	YES
Works with Wall Control:	YES
Reversible:	YES
Included Remote Control:	RC1000
Included Wall Control:	
Smart Control:	YES
Compatible Remote Control(s):	
Compatible Wall Control(s):	WC1000
Compatible Smart Control:	BD-1000

## SHIPPING

Carton Width:	18.13	
Carton Height:	8.88	
Carton Length:	37.25	
Carton Weight:	25.7	
Carton Cubic Feet:	3.471	
Small Package Shippable:	YES	
Master Pack Width:		
Master Pack Height:		
Master Pack Length:		
Master Pack Weight:		
Master Cubic Feet:		
Multi-Pack:	1	
Master Pack:	1	

<sup>⚠</sup> WARNING: Handling this production expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise bunding this product for more information qo to: www.P55Warningsca.gov.

For additional information, please contact Customer Care: 1-800-221-7977 | Product depicted on this specisheet is protected by United States Federal and/or Stee leavis inducting US Patent, Trademark and/or Copyright and unfail competition laws. Unauthorized reproduction or use carries severe legal penalties.

Rev03.21.2025 09:58 AM