



Image File Name: F676L-CL.jpg

### MEASUREMENTS

Blade Finish:	
Blade Material:	ABS
Blade Sweep:	44"
No. of Blades:	3
Blade Pitch:	21
Reversible Blades:	NO
Slope:	YES
Hanging Weight:	11.51
Downrod 1:	6
Downrod 1 Outside Dia:	.75
Downrod 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	14.75
Ceiling to Blade (Dim B):	9.75
Lead Wire:	80"
Power:	AC
Motor Size:	AC 153 X 15 MM

	Low	Low/Med.	Medium	Med/High	High
RPM	84				171
Amps	0.22				0.44
Watts	13.35				52.91
CFM	1354.0				3278.0
CFM/Watts	101.42				61.95

### LAMPING

No. of Bulbs:	1
Max Bulb Wattage:	16
Light Type:	Z42 LED
Light Kit Optional:	NO
Socket:	Y40 LED MODULE
Integrated Light Kit:	YES
Dimmable:	NO
Ballast:	
Rated Life Hours:	30000
Uplight:	NO
Bulb/LED Included:	YES
Color Temp.:	3000
CRI:	94
Initial Lumens:	1511.4
Delivered Lumens:	1008.2

## Vital - LED 44" Ceiling Fan

Item #:	F676L-CL
UPC Code:	706411064241
Product Family Name:	Vital
Finish:	Coal
Category:	INTERIOR FAN
Category Type:	Ceiling Fan
Certification:	4000048
Patents:	
Notes:	*IF PURCHASING OPTIONAL CONTROLS RCS213 OR WCS213 MUST ALSO PURCHASE RECEIVER L0010460001

LED

LED



ETL Intertek

### GLASS

Description:	FROSTED WHITE
Material:	PC LENS
Part No.:	
Quantity:	1
Width:	5.75
Height:	1.25
Length:	

### CONTROLS

Pull Chain Control:	YES
Works with Remote Control:	YES
Works with Wall Control:	YES
Reversible:	YES
Included Remote Control:	
Included Wall Control:	
Smart Control:	NO
Compatible Remote Control(s):	RCS213 *SEE NOTES
Compatible Wall Control(s):	WC116L, WCS213 *SEE NOTES
Integrated Smart Control:	
Compatible Smart Control:	

### SHIPPING

Carton Width:	8.63
Carton Height:	9.5
Carton Length:	23.38
Carton Weight:	14.59
Carton Cubic Feet:	1.109
Small Package Shippable:	YES
Master Pack Width:	
Master Pack Height:	
Master Pack Length:	
Master Pack Weight:	
Master Cubic Feet:	
Multi-Pack:	1
Master Pack:	1

⚠ WARNING: Handling this product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise touching this product. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

For additional information, please contact Customer Care: 1-800-221-7977 | Product depicted on this spec sheet is protected by United States Federal and/or State laws including US Patent, Trademark and/or Copyright and unfair competition laws. Unauthorized reproduction or use carries severe legal penalties.

Rev 01.10.2024 01:45 PM