



MEASUREMENTS

Blade Finish:	
Blade Material:	PLYWOOD WITH PAPER OVERLAY
Blade Sweep:	52"
No. of Blades:	5
Blade Pitch:	12
Reversible Blades:	NO
Slope:	YES
Hanging Weight:	16.09
Downrod 1:	6
Downrod 1 Outside Dia:	.75
Downroad 2:	
Downrod 2 Outside Dia:	
Ceiling to Lowest Point: (Dim A):	14.5
Ceiling to Blade (Dim B):	11.0
Lead Wire:	80"
Power:	AC
Motor Size:	AC 153 X 17 MM

	Low	Low/Med.	Medium	Med/High	High
RPM	72				170
Amps	0.24				0.53
Watts	13.0				63.8
CFM	1946.0				4762.0
CFM/Watts	149.69				74.64

LAMPING

No. of Bulbs:	1
Max Bulb Wattage:	
Light Type:	Z59 LED
Light Kit Optional:	NO
Socket:	Y54 LED MODULE
Integrated Light Kit:	YES
Dimmable:	NO
Ballast:	
Rated Life Hours:	30000
Uplight:	NO
Bulb/LED Included:	YES
Color Temp.:	3000
CRI:	94
Initial Lumens:	1417.1
Delivered Lumens:	878.3

Airetor - LED 52" Ceiling Fan

Item #:	F673L-WHF
UPC Code:	706411064524
Product Family Name:	Airetor
Finish:	Flat White
Category:	INTERIOR FAN
Category Type:	Ceiling Fan
Certification:	4000048
Patents:	

Notes:





GLASS

Description:	FROSTED WHITE
Material:	GLASS
Part No.:	
Quantity:	1
Width:	8.5
Height:	0.75
Length:	8.5

CONTROLS

Pull Chain Control:	YES
Works with Remote Control:	NO
Works with Wall Control:	YES
Reversible:	YES
Included Remote Control:	
Included Wall Control:	
Smart Control:	NO
Compatible Remote Control(s):	
Compatible Wall Control(s):	WC116L
Compatible Smart Control:	

SHIPPING

Carton Width:	11.63	
Carton Height:	12.25	
Carton Length:	24.75	
Carton Weight:	21.12	
Carton Cubic Feet:	2.041	
Small Package Shippable:	YES	
Master Pack Width:		
Master Pack Height:		
Master Pack Length:		
Master Pack Weight:		
Master Cubic Feet:		
Multi-Pack:	1	
Master Pack:	1	

MaRNING: Handling this product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise bushing his product for more information go to view. P65Warnings.ca.gov.

For additional information, please contact Customer Care:1-800-221-7977 | Product depicted on this specisheet is protected by United States Federal and/or State laws including US Patent Trademark and/or Copyright and unfair competition laws. Unauthorized reproduction or use carries severe legal penalities.

Rev03.14.202512:35 PM